

Page 1/10

Fax: 0049-(0)7223-284-245

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU Sprühkleber
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

email: sds@uhu.boltongroup.com

· Further information obtainable from: UHU QESH

· 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

(Contd. of page 1)

P210 Keep away from open flames. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

Adhesive

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-****	dimethyl ether ❖ Flam. Gas 1, H220; ❖ Acute Tox. 2, H330; Press. Gas C, H280	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-XXXX	butane ♦ Flam. Gas 1, H220; ♦ Acute Tox. 3, H331; Press. Gas C, H280	10-25%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol The Flam. Liq. 2, H225; The Eye Irrit. 2, H319	2.5-10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-XXXX	propane	2.5-10%

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation: No special measures required.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B

(Contd. on page 4)



Page 4/10



Safety data sheet according to 1907/2006/EC, Article 31

Version number 27 Revision: 26.06.2019 Printing date 26.06.2019

Trade name: UHU Sprühkleber

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Contro	ol para	meters	
Ingredien	ts with	limit values that require mon	itoring at the workplace:
115-10-6	dimeth	yl ether	
IOELV (El	J)	Long-term value: 1920 mg/m³,	1000 ppm
AGW (Ger	rmany)	Long-term value: 1900 mg/m³, 8(II);DFG, EU	1000 ppm
106-97-8 l	butane		
AGW (Ger	rmany)	Long-term value: 2400 mg/m³, 4(II);DFG	1000 ppm
64-17-5 et	thanol		
AGW (Ger	rmany)	Long-term value: 380 mg/m³, 2 4(II);DFG, Y	00 ppm
74-98-6 pı	ropane		
AGW (Ger	rmany)	Long-term value: 1800 mg/m³, 4(II);DFG	1000 ppm
·DNELs			
64-17-5 et	thanol		
Oral Consumer DNEL, longterm oral 87 mg/kg bw/day (.)		87 mg/kg bw/day (.)	
Dermal	Consu	mer DNEL, longterm dermal	206 mg/kg bw/day (.)
Inhalative	Consu	mer DNEL, acute inhalation	950 mg/m³ (.)
	Consu	mer DNEL, longterm inhalation	114 mg/m³ (.)

· PNECs

64-17-5 ethanol

PNEC Fresh water 0.96 mg/l (.) PNEC Marine water 0.79 mg/l (.)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter AX

(Contd. on page 5)





Safety data sheet according to 1907/2006/EC, Article 31

Version number 27 Revision: 26.06.2019 Printing date 26.06.2019

Trade name: UHU Sprühkleber

· Protection of hands:

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Not required.

SECTION 9: Physical and chemical properties

· 9.1	Informat	ion on	basic p	hysica	l and c	hemica	l properties
-------	----------	--------	---------	--------	---------	--------	--------------

General Information

Appearance:

Form: Aerosol Colour: **Transparent** Characteristic · Odour: · Odour threshold: Not determined. Not determined. · pH-value:

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: -44.5 °C

-35 °C · Flash point:

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

 Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Not determined.

· Explosion limits:

· Vapour pressure at 20 °C:

Lower: 1.5 Vol % Upper: 18.6 Vol % 5200 hPa

(Contd. on page 6)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

	(Contd. of page
Density at 20 °C:	0.63451 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	91.0 %
Solids content:	9.0 %
9.2 Other information	All relevant physical data were determined for th mixture. All non determined data are not measurably on the relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

		•	•	
	· LD/LC50	values rele	levant for classification:	
	115-10-6	dimethyl e	ether	
	Inhalative	LC50/4 h	308 mg/l (rat)	
	106-97-8 I	butane		
	Inhalative	LC50/4 h	658 mg/l (rat)	
	64-17-5 et	thanol		
	Oral	LD50	7060 mg/kg (rat)	
_		•	(Cont	td. on page 7)

EU-EN



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

(Contd. of page 6)

Inhalative LC50/4 h 20000 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

EU-EN





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

(Contd. of page 7)

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	1950 DRUCKGASPACKUNGEN AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
3	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
<u>^</u>	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	N
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler): EMS Number:	- F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
otomago coac	SW22 For AEROSOLS with a maximum capaci
	of 1 litre: Category A. For AEROSOLS with
	capacity above 1 litre: Category B. For WAST
Segregation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capaci
Segregation code	of 1 litre:
	Segregation as for class 9. Stow "separated fron
	class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision class 2.

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

	(Contd. of page 8
	Segregation as for the appropriate subdivision o class 2.
· 14.7 Transport in bulk according to a of Marpol and the IBC Code	Annex II Not applicable.
· Transport/Additional information:	
· ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
,	Not permitted as Excepted Quantity
· Transport category	2
Tunnel restriction code	D
·IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
,	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

· Department issuing SDS: UHU QESH

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.06.2019 Version number 27 Revision: 26.06.2019

Trade name: UHU Sprühkleber

(Contd. of page 9)

· Contact: Dr. C. Hanf

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 3: Acute toxicity – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

* Data compared to the previous version altered.

FU-FN